

R6 Series Three Phase On-grid Inverter

R6 series is the SAJ's middle to high output platform on on-grid solar inverter, with good efficiency, AFCI optional, 110% AC overload and stable remote control connection. R6 covers 5-50kW, 2-4MPPTs and both single and three phase grid.



- ❑ AFCI(Optional)
- ❑ String current up to 16A
- ❑ Max. efficiency 98.8%
- ❑ Built-in AC & DC SPD
- ❑ 110% AC overloading
- ❑ Safety & reliability

R6-15K-T2-32 | R6-17K-T2-32 | R6-20K-T2-32
R6-22K-T2-32 | R6-25K-T2-32-B | R6-25K-T2-32

MODEL	R6-15K-T2-32	R6-17K-T2-32	R6-20K-T2-32	R6-22K-T2-32	R6-25K-T2-32-B	R6-25K-T2-32
DC Input						
Max. PV Array Power [Wp]@STC	22500	25500	30000	33000	37500	37500
Max. DC Voltage [V]	1100					
MPPT Voltage Range [V]	180 ~ 1000					
Rated DC Voltage [V]	600					
Start Voltage [V]	200					
Min. DC Voltage [V]	180					
Max. DC Input Current [A]	32/32					
Max. DC Short Circuit Current [A]	38.4/38.4					
No. of Strings per MPPT	2/2					
No. of MPPT	2					
DC Switch	Integrated					
AC Output						
Rated AC Power [W]	15000	17000	20000	22000	25000	25000
Max. Apparent Power*[VA]	16500	18700	22000	24200	25000	27500
Rated Output Current [A]@230Vac	21.7	24.6	29	31.9	36.2	36.2
Max. Output Current [A]	25	28.3	33.3	36.7	37.9	41.7
Rated AC Voltage/Range [V]	3+N+PE, 220/380, 230/400, 240/415; 180 ~ 280/312 ~ 485					
Rated Output Frequency/Range [Hz]	50,60/45 ~ 55,55 ~ 65					
Power Factor [cos ϕ]	0.8 leading ~ 0.8 lagging					
Total Harmonic Distortion [THDi]	<3%					
Efficiency						
Max. Efficiency	98.8%					
Euro Efficiency	98.5%					
Protection						
Internal Overvoltage Protection	Integrated					
DC Insulation Ristance Detection	Integrated					
Grid Monitoring	Integrated					
GFCI Monitoring	Integrated					
DCI Monitoring	Integrated					
AC Short Circuit Current Protection	Integrated					
AC Grounding Detection	Integrated					
DC Surge Protection	Integrated					
AC Surge Protection	Integrated					
Anti-islanding Protection	Integrated					
AFCI Protection	Optional					
Interface						
DC Connection	D4/MC4(Optional)					
AC Connection	Plug-in Connector					
Display	LED+APP					
Communication Port	RS232(USB)+RS485(RJ45)+DRM					
Communication	Wi-Fi/Ethernet/4G(Optional)					
General Parameters						
Topology	Non-isolated					
Consumption at Night [W]	<1					
Operating Temperature Range	-40°C to +60°C (45°C to 60°C with derating)					
Cooling Method	Intelligent Fan cooling					
Ambient Humidity	0-100% Non-condensing					
Altitude	4000m (>3000m Power Derating)					
Noise [dBA]	<50					
Ingress Protection	IP65					
Mounting	Wall Mounting					
Dimensions [H*W*D] [mm]	409*558*234.5					
Weight [kg]	22.5					
Warranty [Year]	10					
Applicable Standard	EN 62109-1/2, EN 61000-6-1/2/3/4, EN 50438, EN 50549, C10/11, IEC 62116, IEC 61727, RD 1699, RD 413, UNE 206006, UNE 206007, NTS, CEI 0-16, CEI 0-21, AS 4777.2, NBR 16149, NBR 16150, VDE-AR-N 4105, VDE 0126-1-1					

Remarks: *1 According to C10/C11, Max. Apparent Power= Rated AC Power.